

# 21080 Lube Skid



## TANKS

- (1) 80 gallon ASME tank – Used Oil
- (4) 30 gallon ASME tanks – Fresh Oil & Fluids

## POWER

18.5 CFM vacuum /compressor driven by 8HP electric start Honda gas engine – 125 psi max

## HOSES & REELS

- (1) 1" x 50' Used Oil Hose on Spring Retractable Reel
- (1) 5/8" x 50' Fresh Oil Hose on Spring Retractable Reel
- (3) 3/4" x 50' Fresh Oil Hoses on Spring Retractable Reels
- 3/8" x 50' Air Hose on Spring Retractable Reel
- 1" x 20' Used Oil Offload Hose

## HOSE ENDS, METERS, HANDLES

Used Oil Hose – 1" cam and groove fitting  
Fresh fluid hoses – 1/2" flush face quick disconnects, Adaptable to Meters (priced separately, specify quantity and type)

## FRAME

3" x 6" tubing for transporting  
17 gallon drain pan

## SAGE OIL VAC FEATURES

All fresh fluid tanks equipped with in line filter – 25 micron standard  
Patented vacuum process to load fresh fluid tanks, (Barrel Straws priced separate, specify quantity and length)  
Patented Used Filter Receptacle, plumbed to used oil tank  
Patented Filter Stinger – oil filter puncture and evacuate before removal (priced separate)  
Control Panel  
All tank and compressor controls are remoted to Control Panel at back of skid

## DIMENSIONS AND WEIGHTS

Width: 4' 1" / (1.24m)  
Length: 10' 1" / (3.07m)  
Empty weight: 2147lbs. / (974 kg)  
Max Operating Weight: 3023 lbs. / (1371 kg)

