

21120 Lube Skid



TANKS

- (1) 120 gallon ASME tank – Used Oil
- (4) 60 gallon ASME tanks – Fresh Oil & Fluids

POWER

18.5 CFM vacuum /compressor driven by 8.0HP electric start Honda gas engine – 125 psi max

HOSES & REELS

- (1) 1" x 50' Used Oil Hose on Spring Retractable Reel
- (1) 5/8" x 50' Fresh Oil Hose on Spring Retractable Reel
- (3) 3/4" x 50' Fresh Oil Hoses on Spring Retractable Reels
- (1) 3/8" x 50' Air Hose on Spring Retractable Reel
- (1) 1" x 20' Used Oil Offload Hose

HOSE ENDS, METERS, HANDLES

Used Oil Hose – 1" cam and groove fitting
Fresh fluid hoses – 1/2" flush face quick disconnects, Adaptable to Meters (priced separately, specify quantity and type)

FRAME

3" x 6" tubing for transporting

SAGE OIL VAC FEATURES

All fresh fluid tanks equipped with in line filter – 25 micron standard
Patented vacuum process to load fresh fluid tanks, (Barrel Straws priced separate, specify quantity and length)
Patented Used Filter Receptacle, plumbed to used oil tank
Patented Filter Stinger – oil filter puncture and evacuate before removal (priced separate)
Control Panel
All tank and compressor controls are remoted to Control Panel at back of skid

DIMENSIONS AND WEIGHTS

Width: 4' 1" / (1.24m)
Length: 11' 2 3/4" / (3.30m)
Empty weight: 2480 lbs. / (1125 kg)
Max Operating Weight: 4232 lbs. / (1920 kg)

