

2M060 Lube Skid



TANKS

- (1) 60 gallon ASME tank – Used Oil
- (1) 60 gallon ASME tank – Fresh Oil & Fluid

POWER

12.5 CFM vacuum /compressor driven by 6.0 HP electric start Robin gas engine

HOSES & REELS

- 3/4" x 25' Used Oil Hose on Spring Retractable Reel
- 5/8" x 25' Fresh Oil Hose on Spring Retractable Reel
- 3/8" x 25' Air Hose
- Integrated Offload Hose

HOSE ENDS, METERS, HANDLES

- Used Oil Hose – 3/4" cam and groove fitting
- Fresh fluid hoses – 1/2" flush face quick disconnects, Adaptable to Meters (priced separately, specify quantity and type)

FRAME

- 6" Channel frame
- Forklift able/ movable when empty

SAGE OIL VAC FEATURES

- All fresh fluid tanks equipped with in line filter – 25 micron standard
- Patented vacuum process to load fresh fluid tanks, (Barrel Straws priced separate, specify quantity and length)
- Patented Used Filter Receptacle, plumbed to used oil tank
- Patented Filter Stinger – oil filter puncture and evacuate before removal (priced separate)
- All tank and compressor controls are remotod to Control Panel at back of skid

DIMENSIONS AND WEIGHTS

- Width: 4' 1" / (1.24m)
- Length: 6' 3 1/8" / (1.91m)
- Height: 3' 7 1/2" / (1.10m)
- Empty weight: 925 lbs. / (420 kg)
- Normal Max Operating Weight 1363 lbs. / (618 kg)

