

10080 Lube Trailer



TANKS

- (1) 80 gallon ASME tank – Used Oil
- (1) 80 gallon ASME tank – Fresh Oil & Fluids

POWER

12.5 CFM vacuum/ compressor driven by 5.5 HP Honda engine - 125 psi max

HOSES & REELS

- (2) 3/4" x 25' Oil Hoses on Spring Retractable Reels
- 3/8" x 25' Air Hose
- 1" x 20' Used Oil Offload Hose

HOSE ENDS, METERS, HANDLES

Used Oil Hose – 3/4" cam and groove fittings
Fresh fluid hoses – 1/2" flush face quick disconnects, Adaptable to Meters (priced separately, specify quantity and type)

FRAME

- Trailer Mounted
- Single 3500# rubber torsion axle
- (2) 225/75R15 tires
- Universal 2" hitch
- Drop leg jack
- Tongue-mounted toolbox (21" x 16" x 34")
- DOT-approved light package
- 4 flat electric adapter

SAGE OIL VAC FEATURES

- All fresh fluid tanks equipped with in line filter – 25 micron standard
- Patented vacuum process to load fresh fluid tanks, (Barrel Straws priced separate, specify quantity and length)
- Patented Used Filter Receptacle, plumbed to used oil tank
- Patented Filter Stinger – oil filter puncture and evacuate before removal (priced separate)

DIMENSIONS AND WEIGHTS

- Width (outside fender to outside fender): 5' 9 1/2" / (1.77m)
- Length: 11' 9" / (3.58m)
- Empty weight: 1520 lbs. / (689 kg)
- Max Operating Weight: 2104 lbs. / (954 kg)

