

# 10120 Lube Trailer



## TANKS

- (1) 120 gallon ASME tank – Used Oil
- (1) 120 gallon ASME tank – Fresh Oil & Fluid

## POWER

12.5 CFM vacuum/ compressor driven by 5.5 HP Honda engine - 125 psi max

## HOSES & REELS

- (2) 3/4" x 25' Oil Hoses on Spring Retractable Reels
- 3/8" x 25' Air Hose
- 1" x 20' Used Oil Offload Hose

## HOSE ENDS, METERS, HANDLES

Used Oil Hose – 3/4" cam and groove fittings  
Fresh fluid hoses – 1/2" flush face quick disconnects, Adaptable to Meters (priced separately, specify quantity and type)

## FRAME

- Trailer Mounted
- Single 5200# spring leaf axle with electric brakes
- (2) 225/75R15 tires
- Universal 2" hitch
- Drop leg jack
- Tongue-mounted toolbox (21" x 16" x 43")
- DOT-approved light package
- 7 plug electric adapter

## SAGE OIL VAC FEATURES

- All fresh fluid tanks equipped with in line filter – 25 micron standard
- Patented vacuum process to load fresh fluid tanks, (Barrel Straws priced separate, specify quantity and length)
- Patented Used Filter Receptacle, plumbed to used oil tank
- Patented Filter Stinger – oil filter puncture and evacuate before removal (priced separate)

## DIMENSIONS AND WEIGHTS

- Width: 6' 9 1/8" / (2.05m)
- Length: 13' 2" / (4.01m)
- Empty weight: 2165 lbs. / (982 kg)
- Max Operating Weight: 3041 lbs. / (1379 kg)

