

11120 Lube Trailer



TANKS

- (1) 120 gallon ASME tank – Used Oil
- (3) 60 gallon ASME tanks – Fresh Oil & Fluid
- (1) 60 gallon ASME epoxy-lined tank – Coolants

POWER

18.5 CFM vacuum/ compressor driven by electric start 8.0 HP Honda engine - 125 psi Max

HOSES & REELS

- (1) 1" x 50' Used Oil Hose on Spring Retractable Reel
- (1) 5/8" x 50' Fresh Oil Hose on Spring Retractable Reel
- (3) 3/4" x 50' Fresh Oil Hoses on Spring Retractable Reels
- 3/8" x 50' Air Hose and Reel
- 1 1/2" x 20' Used Oil Offload Hose

HOSE ENDS, METERS, HANDLES

Used Oil Hose – 1" cam and groove fittings
Fresh fluid hoses – 1/2" flush face quick disconnects, Adaptable to Meters (priced separately, specify quantity and type)

FRAME

- Trailer Mounted
- Tandem 5200# spring leaf axles with electric brakes
- (4) 225/75R15 tires
- (1) 225/75R15 spare tire with bracket
- Universal 2 5/16" hitch
- Heavy duty drop leg jack
- Tongue-mounted toolbox (24" x 16" x 43")
- Additional passenger side storage box (30" x 24" x 48")
- DOT-approved light package
- 7 prong electric adapter"
- 17 gallon drain pan

SAGE OIL VAC FEATURES

- Reel cabinet with roll up, shutter-style door
- All fresh fluid tanks equipped with in line filter – 25 micron standard
- Patented vacuum process to load fresh fluid tanks, (Barrel Straws priced separate, specify quantity and length)
- Patented Used Filter Receptacle, plumbed to used oil tank
- Patented Filter Stinger – oil filter puncture and evacuate before removal (priced separate)

DIMENSIONS AND WEIGHTS

- Width: 6' 9 3/8" / (2.07m)
- Length: 15' 10" / (4.83m)
- Empty weight: 4300 lbs. / (1950 kg)
- Max Operating Weight: 6052 lbs. / (2745 kg)

