

11160 Lube Trailer



TANKS

- (1) 60 gallon ASME tank – Used Oil
- (3) 60 gallon ASME tank – Fresh Oil & Fluid
- (1) 500 gallon diesel tank
- Duel Element Fuel Filters
- Digital inline meter

POWER

- 18.5 CFM vacuum/ compressor driven by electric start 8.0 HP Honda engine - 125 psi max
- 25 gpm Air Diaphragm Pump for diesel, Auto Shut-off Nozzle

HOSES & REELS

- (1) 1" x 50' Used Oil Hose and Spring Retractable Reel
- (4) 3/4" x 50' Fresh Oil Hoses and Spring Retractable Reels
- (1) 3/8" x 50' Air Hose and Reel
- 1 1/2" x 20' Used Oil Offload Hose

HOSE ENDS, METERS, HANDLES

- Used Oil Hose – 3/4" cam and groove fitting
- Fresh fluid hoses – 1/2" flush face quick disconnects, Adaptable to Meters (priced separately, specify quantity and type)

FRAME

- Trailer Mounted
- Tandem 6000 lb. spring leaf axles with electric brakes
- (4) 225/75R15 tires
- (1) 225/75R15 spare tire with bracket
- Universal 2 5/16" hitch
- Drop leg jack
- Tongue-mounted toolbox (24" x 16" x 43")
- DOT-approved light package
- 7 plug electric adapter
- 17 gallon drain pan

SAGE OIL VAC FEATURES

- Reel cabinet with roll up, shutter-style door
- All fresh fluid tanks equipped with in line filter – 25 micron standard
- Patented vacuum process to load fresh fluid tanks, (Barrel Straws priced separate, specify quantity and length)
- Patented Used Filter Receptacle, plumbed to used oil tank
- Patented Filter Stinger – oil filter puncture and evacuate before removal (priced separate)

DIMENSIONS AND WEIGHTS

- Width: 6' 9" / (2.06 m)
- Length: 19' 4" / (5.89 m)
- Empty weight: 5111 lbs. / (2318 kg)
- Max Operating Weight: 10075 lbs. / (4570 kg)

