

# 11256 Lube Trailer



## TANKS

- (1) 250 gallon ASME tank – Used Oil
- (1) 250 gallon ASME tank – Fresh Oil & Fluid
- (3) 80 gallon ASME tanks – Fresh Oil & Fluid
- (1) 80 gallon ASME epoxy-lined tank – Fresh Oil & Fluid

## POWER

20 CFM vacuum/ compressor driven by electric start 8 HP Honda engine - 175 psi max

## HOSES & REELS

- (1) 1" x 50' Used Oil Hose and Spring Retractable Reel
- (1) 5/8" x 50' Fresh Oil Hoses and Spring Retractable Reels
- (4) 3/4" x 50' Fresh Oil Hoses and Spring Retractable Reels
- 3/8" x 50' Air Hose and Reel
- 1 1/2" x 20' Used Oil Offload Hose

## HOSE ENDS, METERS, HANDLES

Used Oil Hose – 3/4" cam and groove fitting  
Fresh fluid hoses – 1/2" flush face quick disconnects, Adaptable to Meters (priced separately, specify quantity and type)

## FRAME

- Trailer Mounted
- Tandem 7000 lb. spring leaf axles with electric brakes
- (4) 225/75R16 tires
- (1) 225/75R16 spare tire with bracket
- Universal 2 5/16" hitch
- Drop leg jack
- Tongue-mounted toolbox (24" x 16" x 43")
- DOT-approved light package
- 7 plug electric adapter
- 17 gallon drain pan

## SAGE OIL VAC FEATURES

- Reel cabinet with roll up, shutter-style door
- All fresh fluid tanks equipped with in line filter – 25 micron standard
- Patented vacuum process to load fresh fluid tanks, (Barrel Straws priced separate, specify quantity and length)
- Patented Used Filter Receptacle, plumbed to used oil tank
- Patented Filter Stinger – oil filter puncture and evacuate before removal (priced separate)

## DIMENSIONS AND WEIGHTS

- Width: 6' 9 1/2" / (2.07 m)
- Length: 22' 9" / (6.93 m)
- Empty weight: 5960 lbs. / (2703 kg)
- Max Operating Weight: 10121 lbs. / (4591 kg)

