

17397 Lube Trailer



TANKS

- (1) 390 gallon ASME tank – Used Oil
- (1) 390 gallon ASME tank – Fresh Oil & Fluid
- (1) 80 gallon ASME tanks – Fresh Oil & Fluid
- (1) 80 gallon ASME epoxy-lined tank – Fresh Oil & Fluid
- (1) 60 gallon ASME tank- Fresh Oil & Fluid
- (1) 60 gallon ASME tank- Fresh Oil & Fluid
- (1) 60 gallon ASME tank- Fresh Oil & Fluid
- 50:1 grease system for 120# grease drum

POWER

20 CFM vacuum/ compressor driven by electric start 13 HP Honda engine - 125 psi max

HOSES & REELS

- (1) 1 1/2" x 75' Used Oil Hose and Spring Retractable Reel
- (2) 3/4" x 75' Fresh Oil Hoses and Spring Retractable Reel
- (1) 3/8" x 100' Grease Drum Hose and Retractable Reel
- (3) 5/8" x 75' Fresh Oil Hoses and Spring Retractable Reel

HOSE ENDS, METERS, HANDLES

Used Oil Hose – 1" cam and groove fittings
Fresh fluid hoses – 1/2" flush face quick disconnects, Adaptable to Meters (priced separately, specify quantity and type)

FRAME

- Trailer Mounted Gooseneck Hitch
- Tandem 8000 lb spring leaf axles with electric brakes
- (4) 215/75R17.5 16 ply tires
- (1) 215/75R17.5 spare tire with bracket
- Universal 2 5/16" hitch
- LED lighting
- Diamond plated steps
- (2) Storage Boxes (60" x 60" x 36")
- 2" DOT-approved reflective tape placed on sides of trailer
- 7 plug electric adapter
- 17 gallon drain pan

SAGE OIL VAC FEATURES

- Reel cabinet with lighting, lockable
- All fresh fluid tanks equipped with in line filter – 25 micron standard
- Patented vacuum process to load fresh fluid tanks, (Barrel Straws priced separate, specify quantity and length)
- Patented Used Filter Receptacle, plumbed to used oil tank
- Patented Filter Stinger – oil filter puncture and evacuate before removal (priced separate)
- Flood lights for work areas
- Hose cradle

DIMENSIONS AND WEIGHTS

Width: 7' 9 1/2" / (2.37 m)

Length: 31' 5" / (9.58 m)

Empty weight: 9000 lbs / (4082 kg)

Max Operating Weight: 14449 lbs / (6554 kg)

